

project specification

fixture type **D643 LV6.5** incandescent cove light **D172-6.5** incandescent under cabinet

Job Name:
 Job Nbr:
 Tag:
 Distributor:
 Electrician
 Engineer:
 Interior Design:
 Architect:
 note: site measurements required

Note:
 Any Changes or modifications to mmj lighting 96 ltd lighting fixtures, must be done in the mmj lighting 96 ltd factory.
 Any modifications or changes done in the field will void all warranties and approvals.




D172-6.5

note: illustrated above as under cabinet fixture :
 [D115 extrusion and D115-c lens = 120v hardwired].

Power feed: right, left.

- D172-6.5 - 1x 20 w overall length: 10"
- D172-6.5 - 2x 20 w overall length: 18"
- D172-6.5 - 3x 20w overall length: 24"
- D172-6.5 - 4x 20w overall length: 30"



D643 LV6.5 Cove light elevation

D643 LV6.5 section

section

fixture number	description	spacing	watts per lamp	lamps	watts per strip	lumens/lamp	rated hours
D643-1-20w	LV 6.5 - 8" incandescent cove light 120v	8"	20	1	20	87	6500
D643-1-25w	LV 6.5 - 8" incandescent cove light 120v	8"	25	1	25	245	1000
D643-1-40w	LV 6.5 - 8" incandescent cove light 120v	8"	40	1	40	440	750
D643-3-20w	LV 6.5 - 24" incandescent cove light 120v	8"	20	3	60	87	6500
D643-3-25w	LV 6.5 - 24" incandescent cove light 120v	8"	25	3	75	245	1000
D643-3-40w	LV 6.5 - 24" incandescent cove light 120v	8"	40	3	120	440	750
D643-6-20w	LV 6.5 - 48" incandescent cove light 120v	8"	20	6	120	87	6500
D643-6-25w	LV 6.5 - 48" incandescent cove light 120v	8"	25	6	150	245	1000
D643-6-40w	LV 6.5 - 48" incandescent cove light 120v	8"	40	6	240	440	750
Accessories							
R100	8" reflector - one per lamp						
D171 IJ	internal joiner for straight runs						
D171 F	flex joiner for curved or round applications						
note	all lengths are wired for row mounting						

D643 LV6.5 shop drawing 06.14.07 c 